

SAFETY DATA SHEET

577

Page: 1 Compilation date: 22/01/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 577

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Mouldpro ApS Baltorpbakken 10 2750 Ballerup Denmark

Tel: +45 70 20 31 31

Email: robert@mouldpro.com

1.4. Emergency telephone number

Emergency tel: +45 70 20 31 31

(office hours only)

Section 2: Hazards identification

2.1. Classification of the subs	stance or mixture		
Classification under CLP:	STOT SE 3: H335; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin		
	Sens. 1A: H317; -: EUH208		
Most important adverse effects:	Contains hydroquinone monomethyl ether. May produce an allergic reaction. Causes		
	skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May		
	cause respiratory irritation. Toxic to aquatic life with long lasting effects.		
2.2. Label elements			
Label elements:			
Hazard statements:	EUH208: Contains hydroquinone monomethyl ether. May produce an allergic reaction.		
	H315: Causes skin irritation.		
	H317: May cause an allergic skin reaction.		
	H319: Causes serious eye irritation.		
	H335: May cause respiratory irritation.		
	H411: Toxic to aquatic life with long lasting effects.		

577

Page: 2

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental



Signal words: Warning

-	-
Precautionary statements:	P271: Use only outdoors or in a well-ventilated area.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P312: Call a POISON CENTER/doctor//if you feel unwell.
	P321: Specific treatment (see instructions on this label).
2.3. Other hazards	

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DODECYL METHACRYLATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
205-570-6	142-90-5	-	Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	1-10%

2-CARBOXYETHYL ACRYLATE

246-359-9	24615-84-7	-	Skin Corr. 1B: H314	1-10%
CUMENE HYD	ROPEROXIDE			
201-254-7	80-15-9	-	Org. Perox. EF: H242; Acute Tox. 3: H331; Acute Tox. 4: H312; Acute Tox. 4: H302; STOT RE 2: H373; Skin Corr. 1B: H314	1-10%

N,N-DIMETHYL-P-TOLUIDINE

202-805-4	99-97-8	-	Acute Tox. 3: H331; Acute Tox. 3: H311;	<1%
			Acute Tox. 3: H301; STOT RE 2: H373;	
			Aquatic Chronic 3: H412	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

577

Page: 3

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

577

Page: 4

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Polyethylene. Do not use steel containers.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area. The floor of the storage room must be
impermeable to prevent the escape of liquids.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Protective gloves.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Paste
Colour:	Yellow
Odour:	Characteristic odour
Evaporation rate:	No data available.
Oxidising:	No data available.
Solubility in water:	Slightly soluble
Also soluble in:	Most organic solvents.
Viscosity:	Viscous
Kinematic viscosity:	~90000

577

Viscosity test method:	Cone and Plate @ 25°C (CPs)		
Boiling point/range°C:	>35	Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	>93	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	1.10	pH:	Not applicable.
VOC g/l:	No data available.		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DODECYL METHACRYLATE

IPR	MUS	LD50	25	gm/kg
IPR	RAT	LD50	12	gm/kg

CUMENE HYDROPEROXIDE

ORL MUS LDLO 5 gm/kg

Page: 5

577

ORL	RAT	LD50	382	mg/kg
SCU	RAT	LD50	382	mg/kg

N,N-DIMETHYL-P-TOLUIDINE

IPR MUS	LD50	212	mg/kg
---------	------	-----	-------

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Page: 6

577

Page: 7

NB: The user's attention is drawn to the possible existence of regional or national

Marine pollutant: No

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3077

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH208: Contains <name of="" sensitising="" substance="">. May produce an allergic reaction.</name>
	H242: Heating may cause a fire.
	H301: Toxic if swallowed.
	H302: Harmful if swallowed.
	H311: Toxic in contact with skin.
	H312: Harmful in contact with skin.
	H314: Causes severe skin burns and eye damage.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.

577

Page: 8

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H335: May cause respiratory irritation.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.